



APPLICATION:
E2

LEGACY MODEL:
n/a

Code	Size /Dimension	Ply /Plis	L.I.	S.R/Indice de vitesse	Rim/Largeur d e jante (po)	N.S. 32 ^{nds}	O.D. in.	S.W. in.	S.L.R. in.	R.C.	L.C.C. (1X) lbs.@psi	WT. lbs.
819188-74	385/95R25	***	170	F	10.00/1.5	30	53.7	15.3	23.7	-	13,200@130	357
-	445/95R25	***	177	F	11.25/2.0	33	58.5	17.5	25.6	-	16,100@130	-

RUBBER COMPOUND:	
CUT RESISTANT	
HEAT RESISTANT	X
STANDARD	

COMPOSÉ DE CAOUTCHOUC :	
RÉSISTANT AUX COUPURES	
RÉSISTANT À LA CHALEUR	X
NORMAL	

The Aeolus AR28 is engineered for use in mobile crane applications, and specifically for use on mobile cranes. DOT approved and well suited for high speed use, the AR28 features a non-directional tread pattern that reduces road noise. Asymmetrical lug tread pattern provides outstanding traction, and road stability. Heat resistant rubber compound reduces tire damage and downtime.

Features and Benefits:

- DOT Approved
- Heat resistant compound provides excellent tread life
- Exceptional Stability
- Non-directional tread design reduces road noise
- On/Off road applications

Applications:

- Mobile Cranes

L'Aeolus AR28 est expressément conçu pour être utilisé sur des grues mobiles. Approuvé D.O.T. et bien adapté pour les grandes vitesses, le AR28 est doté d'un motif de bande non directionnel qui permet de réduire le bruit de la route. Les barrettes asymétriques fournissent une traction exceptionnelle et de la stabilité sur la route. Le composé de gomme résistant réduit les dommages et les temps d'arrêt.

Caractéristiques et avantages :

- Approuvé D.O.T.
- Le composé de gomme fournit une excellente durée de vie
- Stabilité exceptionnelle
- Le motif de bande non directionnel réduit le bruit de la route
- Utilisations sur route/hors route

Utilisations :

- Grues mobiles

