

## Technical data

# HD 10 VO



**Tandem rollers Series HD CompactLine** | **H230**  
Tandem roller with vibration and oscillation drum

### HIGHLIGHTS

- > Simple, intuitive and language-neutral operation
- > Ergonomic driver platform
- > Excellent view of the drum edges, the machine and the construction site surroundings
- > Compact dimensions
- > Compaction with oscillation

**TECHNICAL DATA HD 10 VO (H230)**

<b>Weights</b>		
Operating weight with ROPS	kg	2525
Max. operating weight	kg	3240
Static linear load, front/rear	kg/cm	12,1/13,2
French classification, value/class		12,1/PV3
<b>Machine dimensions</b>		
Total length	mm	2530
Total height with ROPS	mm	2475
Height loading, min.	mm	1752
Centre distance	mm	1700
Total width	mm	1110
Maximum working width	mm	1050
Ground clearance, centre	mm	280
Kerb clearance, left/right	mm	570/570
Turning radius, inside	mm	2470
<b>Drum dimensions</b>		
Drum width, front/rear	mm	1000/1000
Drum diameter, front/rear	mm	720/720
Drum thickness, front/rear	mm	15/15
Drum type, front		Smooth/non-split
Drum type, rear		Smooth/non-split
Track offset, left/right	mm	0/50
<b>Diesel engine</b>		
Manufacturer		KUBOTA
Model		D1703
Cylinders, quantity		3
Power ISO 14396, kW/PS/rpm		18,5/25,2/2200
Power SAE J1349, kW/HP/rpm		18,5/24,8/2200
Exhaust emission standard		EU Stage V / EPA Tier 4
Exhaust gas after-treatment		-
<b>Travel drive</b>		
Speed, infinitely variable	km/h	10,2
Gradeability, with/without vibration	%	35/40
<b>Vibration</b>		
Vibration frequency, front, I/II	Hz	65/51
Amplitude, front, I/II	mm	0,45/0,45
Centrifugal force, front, I/II	kN	33/20
<b>Oscillation</b>		
Oscillation force, rear, I/II	kN	39/23
Oscillation frequency, rear, I/II	Hz	38/29
Tangential amplitude, rear, I/II	mm	1,34/1,34
<b>Steering</b>		
Swing angle +/-	°	8
Steering, type		Articulated steering
<b>Water-sprinkling system</b>		
Water sprinkling, type		Pressure
<b>Tank capacity/filling capacity</b>		
Fuel tank, capacity	L	42

**Tank capacity/filling capacity**

Water tank, capacity	L	180
<b>Sound level</b>		
Sound power level L(WA), guaranteed	db(A)	106
Sound power level L(WA), representative measurement	db(A)	104

**EQUIPMENT**

12 V power socket | 3-point articulation | Dashboard with displays, indicator lights and switches | Dashboard cover, lockable and weather-resistant | Pressure water sprinkling system | Driver's platform with entry from both sides | Drive lever, left and right | Mechanical battery isolation switch | Vibration-isolated driver's platform | Track offset, mechanical | Automatic vibration system | Water filter system (3-fold) | Central lifting bracket | Central water outlet

**OPTIONAL EQUIPMENT**

Plastic scraper, folding | ROPS, foldable | Plastic tarpaulin | Edge pressing and cutting equipment | Back-up alarm | Working spotlights | Battery isolation switch with cable control actuation | V-belt protection